



PT Ltd.

Innovative Measurement Electronics



WS5 PRECISION BALANCE

FEATURES

- 1/30,000 display resolution typical
- Simple calibration
- 13 weighing units available (gram, carat, pound, ounce, dram, grain, troy, penny, weight, momme, tora, tael (HK jewelry), tael (TW), tael (HK))
- Default units selectable
- Large LCD display with LED back light
- Back light mode setting, digital filter setting
- Adjustable gravity constant and external weight calibration
- 1/15,000 non linearity for 1/30,000 display resolution
- Bi-directional RS-232 interface and plastic shield
- Low power status indication
- Auto power off with timer setting



SPECIFICATIONS

- Operating Temperature: 0°C~40°C (32°F ~ 104°F)
- Power Source: AC 110V/230V (+10%) Or 4x UM-2 dry cell batteries (batteries not included)
- Display: LCD, 6 Digits. 16mm high
Plastic shield 80mm high

OPTIONS

- Real Time Clock (RTC) Card

ORDERING INFORMATION

Model	Size (WxLxHmm)	Capacity	Division	Resolution	Weight(kg)	Part Number
WS5-150	175x226x56	150g	0.005g	1/30,000	1.7	J07040150G0XXX
WS5-300	176x226x56	300g	0.01g	1/30,000	1.7	J07040300G0XXX
WS5-600	177x226x56	600g	0.02g	1/30,000	1.7	J07040600G0XXX
WS5-1200	178x226x56	1200g	0.02g	1/30,000	1.7	J07041200G0XXX
WS5-1500	179x226x56	1500g	0.05g	1/30,000	1.7	J07045000G0XXX
WS5-3000	180x226x56	3000g	0.1g	1/30,000	1.7	J07043000G0XXX

Due to PT's policy of continuous development, these specifications are subject to change without notice



<http://www.pt-global.com>

